

Construction: Inner Layer: Double-ply silicone coated woven fiberglass fabric hose construction with a spring steel wire helix. Outer Layer: Single-ply neoprene impregnated polyester fabric hose construction reinforced with a spring steel wire helix. Insulation: 1-inch fiberglass insulation (R-value=4)

Product Features:

- Insulated Industrial dryer hose
- Combines flexibility with minimal heat loss
- Suited for air handling applications at low positive and low negative pressures
- Good flexibility
- Excellent external abrasion and chemical resistance

Applications: Fume

Temperature Range: Inner layer; -65°F to +550°F, intermittent to 600°F
Outer layer -40°F to +250°F

Sizes I.D. (inches): 1, 1.5, 2, 2.5, 3, 4, 6, and 8.

ID Tolerances: -0.00 to +0.125 Inch

Standard Length: 12 Feet, custom to 25 Feet

Standard Colors: Inner layer: Iron oxide red, Outer layer: Black

End Finish: Plain cut

Markets: Aerospace, Aluminum Refractory, Brick Kilns, Chemical Plants, Cold Air Supply, Diesel/Engine Exhaust, Dryer Hose, Exhaust Systems, Foundries, Fume Exhaust, Garage Exhaust, Glass Drying, Heater, High Temperature Applications, Plastic Bag Machines, Plastics Industry, Safety Equipment, Ventilation

Technical Data:

Size	Approximate	Min Centerline	Compression	Max Recommended	Max Recommended
Inside Diameter (Inches)	Weight Lbs./ft.	Bend Radius (Inches)	Ratio	Negative Pressure (IN./HG)	Positive Pressure (PSI)
1	0.12	1.2	3 to 1	29	30
1.5	0.17	1.8	3 to 1	29	30
2	0.25	2	3 to 1	29	30
2.5	0.3	2.3	3 to 1	29	30
3	0.33	2.5	3 to 1	29	30
3.5	0.4	2.5	3 to 1	29	30
4	0.48	3	5 to 1	27	30
4.5	0.54	3.2	5 to 1	20	30
6	0.62	4	5 to 1	9	19
8	0.79	4	5 to 1	9	14

* Note: Technical data based on 2 ft. straight lengths of hose 72°F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Specifications and/or prices are subject to change without prior notice.
© 2011 Rubber-Cal all rights reserved.

Pricing:

ID Size Inches	1 unit+	5 units+	10 unit+	40 unit+
0.75	-	-	-	-
0.875	-	-	-	-
1	\$272.98	\$237.49	\$225.20	\$204.73
1.25	-	-	-	-
1.5	\$304.65	\$265.04	\$251.33	\$228.48
1.75	-	-	-	-
2	\$359.48	\$312.75	\$296.57	\$269.61
2.25	-	-	-	-
2.5	\$391.00	\$340.17	\$322.57	\$293.25
3	\$422.34	\$367.44	\$348.43	\$316.76
3.5	-	-	-	-
4	\$512.79	\$446.13	\$423.05	\$384.59
4.5	-	-	-	-
5	-	-	-	-
5.5	-	-	-	-
6	\$656.48	\$571.14	\$541.60	\$492.36
7	-	-	-	-
8	*	*	*	*
9	-	-	-	-
10	-	-	-	-
12	-	-	-	-
14	-	-	-	-
16	-	-	-	-

All prices quoted above are per linear foot and in USD\$.
 Sold in 12 ft. sections, custom to 25 ft. available.
 (-) Indicates not available
 (*) Consult sales team for prices & minimums.