

**Construction:** Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix & external wearstrip

**Product Features:**

- Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- Wearstrip offers additional external and drag resistance
- Great compressibility
- Retractability allows for convenient storage and easy transport in a fraction of its fully extended length
- Listed as UL 94 V-0 flame retardant

**Applications:** Recommended for industrial air movement applications.

**Temperature Range:** -65°F to +250°F

**Sizes I.D. (inches):** 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 12, 14, 16, 18, 20, 22, and 24.  
Custom sizes up to 52 Inch ID available

**ID Tolerances:** To 8": -0.00 to +0.125 Inch  
8" and over: -0.00 to +0.250 Inch

**Standard Length:** 25 Feet

**Standard Colors:** Yellow

**Custom colors:** Olive Drab, Tan, Blue, White

**End Finish:** Plain Cut (cuffs and belted end finishes available)

**Markets:** A/C Ventilation, Aircraft, Blower Hose, Chiller, Confined Space Ventilation, Dehumidification, Fans and Blowers, Flame Retardant, Function Tent HVAC, Humidity Control, Laser Engraving, Mining, Pet Training Hose, Smoke Ejectors, Utility Blowers, Ventilation, Wave Pool Blowers

### Technical Data:

Size	Approximate	Min Centerline	Compression	Max Recommended	Max Recommended
Inside Diameter	Weight	Bend Radius	Ratio	Negative Pressure	Positive Pressure
(Inches)	Lbs./ft.	(Inches)		(IN./HG)	(PSI)
4	0.25	3	5 to 1		5.4
6	0.3	3.5	12 to 1		3
8	0.4	5	12 to 1		3
10	0.6	6.5	12 to 1		2.5
12	0.7	7.5	12 to 1		2
14	0.8	8.5	12 to 1		1.7
16	0.9	9.5	12 to 1		1.5
18	1	10.5	12 to 1		1.3
20	1.1	12	12 to 1		1.1
24	1.6	13	12 to 1		1

\* Note: Technical data based on 2 ft. straight lengths of hose 72°F.

**Disclaimer:** The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

### Pricing:

ID Size Inches	25 ft. +	100 ft. +	250 ft. +	500 ft. +
4	\$10.17	\$8.85	\$8.39	\$7.63
4.5	*	*	*	*
5	\$12.31	\$10.71	\$10.16	\$9.23
5.5	*	*	*	*
6	\$13.05	\$11.35	\$10.77	\$9.79
7	*	*	*	*
8	\$13.74	\$11.95	\$11.33	\$10.30
9	*	*	*	*
10	\$16.73	\$14.55	\$13.80	\$12.55
12	\$20.34	\$17.70	\$16.78	\$15.26
14	\$23.64	\$20.56	\$19.50	\$17.73
16	\$27.08	\$23.56	\$22.34	\$20.31
18	\$31.92	\$27.77	\$26.33	\$23.94
20	\$35.97	\$31.30	\$29.68	\$26.98
22	\$40.84	\$35.53	\$33.69	\$30.63
24	\$44.65	\$38.84	\$36.84	\$33.49

All prices quoted above are per linear foot and in USD\$.

Sold in 25 ft. sections.

(\* ) Consult sales team for prices & minimums.

Specifications and/or prices are subject to change without prior notice.

© 2011 Rubber-Cal all rights reserved.